

solis

26 HP



MORE POWER
MORE SAVINGS



A Product Of

SONALIKA
INTERNATIONAL

SOLIS 26



STANDARD FEATURES

Engine	Engine Type HP Category No. of Cylinders Aspiration Cubic Capacity (cc) Rated RPM (+/-25mm) Air cleaner Cold Start Max Torque @ RPM (Nm) Exhaust	Mitsubishi MVS3L2, three Cylinder Engine 26 3 Natural 1318 2700 Dry air cleaner with clogging sensor Yes 75.2@2200 Underhood Downdraft silencer
Transmission	Drive Clutch Gearbox Transmission	4WD Single Clutch 6F+2R Sliding Mesh
Speed (Forward)	Maximum (Speed Km/Hr) Minimum (Speed Km/Hr)	15.58 @ 2700 1.67 @ 2700
Brakes	Brakes Type of actuation Parking Brake	Oil immersed brakes Mechanical Latch Type with Brake Pedals
Differential lock	Differential lock	Yes, Foot Operated
PTO	PTO (rpm) PTO (actuation)	540 & 1000 Mechanical
Steering	Steering	Power
Electrical	Battery Alternator Seven pin trailer socket	12V, 50Ah 12V, 40Amp Yes
Hydraulics	3 point linkage Stay Bars Hydraulic lifting capacity Auxiliary hydraulic circuit Lift rods Liter Per Minute (LPM)	Cat 1-N Check Chain 600Kg 1DA/1SA(optional) Yes 14.85
Safety Switch	Clutch Safety Switch	Yes
Capacity (Itrs)(+/-5%) approx.	Fuel tank (Lit)	26.5
Turning Diameter meter	Turning diameter Without Brakes (m)	4.25 (RHS) 4.77 (LHS)
Tyre	Front Rear	6.00-12 8.3-20
Dimension & Weight(+/-5%)	Weight(kg) Wheel Base (mm) Total Length (mm) Total Width (mm) Height (mm) Up to ROPS Min Ground Clearance (mm) min Front Track (mm) Rear Track (mm)	1020 1560 2705 925 (min) - 1197 (max) 2153 225 894 725 - 997
Others	Fuel Indicator gauge Front Toe Hook Front & rear weights with std. Ballast Trailer hitch ROPS	Yes Yes Front weights-15x2 1. Clevis Hitch2. Swinging, Drawbar (Optional) Foldable
Optional Features	Tyres Agriculture tyres Turf tyres Industrial tyres Cabin	Front tyre - 6-12, Rear tyre: 8.3-20 Front Tyre - 23x8.50-12, Rear tyre - 33x15.50-16.5 Front tyre - 23x8.50-12 Rear tyre- 33x15.50-16.5 Add on-Heater (Verim cabin)



Dealer Stamp

International Tractors Limited

H.O: TERI University Campus, Plot No. 10 Institutional Area, Vasant Kunj, New Delhi-110070 (INDIA).
 Works: Jalandhar Road, Hoshiarpur-146022, Punjab (India). Phone: +91 1882 302220, 302221,
 Fax: +91 1882 302293, E-mail: exports@sonalika.com, Website: www.sonalika.com.

www.facebook.com/SonalikaTractor
www.twitter.com/SonalikaTractor
www.linkedin.com/groups/Sonalika-Tractor