

Solis

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

H26



**THERMO DYNAMICS
BONNET & TWIN
PROJECTOR LAMPS**

**MID & REAR
PTO**

**SEPARATE PEDAL
FOR FORWARD
& REVERSE**

**CRUISE
CONTROL**

**QUICK ATTACH
MOWER**



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**










**STRATEGIC
COLLABORATION
WITH
YANMAR**












THE TOUGHEST PERFORMER «FOR YOUR FIELD»

H26

Solis



FEATURES	H26
ENGINE 	
Engine Type	Mitsubishi 3-Cylinder Diesel Motor
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION 	
Drive	4 WD
Clutch	Wet type clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	HST (2-Stufen Hydrostat)
SPEED (FORWARD) 	
Maximum Speed (Km/Hr)	21.03@2660
Minimum Speed (Km/Hr)	3.18 at low idle 900 erpm, 8.83@rated erpm
BRAKES 	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
Differential Lock 	
Differential Lock	Yes, Foot Operated
PTO 	
PTO (rpm)	Mid PTO- 2100 RPM, Rear 540
PTO (actuation)	Electro hydraulic operated/mechanical selector lever
STEERING 	
Steering	Power steering
ELECTRICAL 	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS 	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DW
Hydraulic Lifting Capacity	600 Kg
Lift Rods	Standard
Litre per Minute(LPM)	16.5

FEATURES		H26	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		22	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		3.05 (RHS), 2.62 (LHS)	
TYRE 			
Front		6.00-12	
Rear		8.30-20	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		1235	
Wheel Base (mm)		1570	
Total Length (mm)		2895	
Total Width (mm)		1215 (max)-1050 (min)	
Height (mm) Up to ROPS		2325	
Min Ground Clearance (mm)		240	
Front Track (mm)		885	
Rear Track (mm)		960	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with std. Ballast		Front weights - 2 x 15 Kg	
Trailer Hitch		Towbar, Drawbar (optional)	
ROPS		Yes	
OPTIONAL FEATURES 			
Cabin Option		Yes	
Tyres			
			
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	GALAXY PRO
6.5/80-12 280/70 R18	25x8.50-14 13.60-16	23x8.50-12 33x15.50-16,5	F - 220/55R12 R - 280/70R16
Front loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

www.solis.dk